

Certificate of Constancy of Performance



Certificate n°: 0757-CPR-277-9041963-1-1

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction products Regulation or CPR), this certificate applies to the construction product

Basis:

EN 16034
EN 14351-1

Pedestrian doorsets with fire resistance characteristics

Trade name

M84 FR

Product description/
specification

Pedestrian doorsets according to EN 14351-1:2006+A2:2016
with fire resistance characteristics according to EN 16034:2014

Classification: see classification reports n°
FIRES-CR-194-21-AUPE dated 05.08.2021
FIRES-CR-195-21-AUPE dated 05.08.2021
FIRES-CR-196-21-AUPE dated 13.09.2021
FIRES-CR-197-21-AUPE dated 13.09.2021

Levels and classes of
performance

According to configuration in **annex 1**

Intended use(s)

- Installation in residential and non-residential construction
- In the case of room partitioning into fire and/or smoke protection sections and/or escape routes

placed on the market
under the name or trade
mark of

MANTZARIS S.A.

14th km Thessaloniki – Lagadas, GR-57200 Lagadas

and produced in the
manufacturing plant(s)

MANTZARIS S.A.

14th km Thessaloniki – Lagadas, GR-57200 Lagadas

Notified body No.
EC-Reference-No.

0757

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s)

EN 14351-1:2006+A2:2016 and EN 16034:2014


under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the **constancy of performance of the construction product**.

This certificate was first issued on 02.06.2023 and will remain valid until 01.06.2026, as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

The use of this certificate and the marking of the products are bound by an existing certification and surveillance contract with the **ift Rosenheim** no. 277 9041963.

Christian Kehrer

Christian Kehrer
Head of notified product certification body
ift Rosenheim
02.06.2023



www.ec.europa.eu

Identity check



www.ift-rosenheim.de/
ift-zertifiziert
ID: F0C-AC5CC

Certificate of constancy of performance

Annex 1
Certificate holder: MANTZARIS S.A.
Date of issue: 02.06.2023



Certificate n°: 0757-CPR-277-9041963-1-1

Product description:

Essential characteristics according to EN 16034	Performance
Fire resistance (in the case of room partitioning into fire and/or smoke protection sections)	NPD / E 15 / E 20 / E 30 / E 45 / E 60 NPD / EW 15 / EW 20 / EW 30 / EW 45 / EW 60 NPD / EI ₂ 15 / EI ₂ 20 / EI ₂ 30 / EI ₂ 45 / EI ₂ 60* NPD / EI ₁ 15 / EI ₁ 20 / EI ₁ 30 / EI ₁ 45 / EI ₁ 60* * differing classification for glass Polflam: NPD / EI ₂ 15 / EI ₂ 20 / EI ₂ 30 / EI ₂ 45 NPD / EI ₁ 15 / EI ₁ 20 / EI ₁ 30 / EI ₁ 45
Smoke control (only for applications where smoke spread limitation is required)	NPD
Ability to release	NPD / Released
Self-closing action (only for self-closing fire and/or smoke protection doors and/or windows)	NPD / C
Durability of ability to release	NPD / Maintain release
Durability of self-closing (only for self-closing fire and/or smoke protection doors and/or windows) – Compared with loss of quality (resistance to repeated opening and closing) – Compared with ageing (corrosion)	NPD NPD / Achieved